

8 / 4CH Compact 960H/720H Recorder



Key Features:

- H.264 High Profile with outstanding quality but less storage size
- Simultaneous record, live, playback, backup, control & remote access
- 960H/Full D1/ Half D1/CIF recording, up to 180/150fps@960H, 240/200fps@Full D1, 480/400fps@Half D1, 480/400fps@CIF
- Smart search & playback
- HDMI / VGA / CVBS output with 3D de interlace & de noise for the best picture quality with resolution up to 1920 x 1080
- 1 set of 3.5" internal HDD (>3TB/HDD) and eSATA/NAS extension
- Digital watermark
- Privacy mask
- Up to 8 alarm inputs
- Ethernet and 3G, with dual streaming support
- DVR browser utility
- Free DDNS server
- Two-way audio capabilities
- Audio broadcasting
- Dynamic electronics maps for CMS
- Remote setup, monitoring, backup, alarm notification & remote software upgrade
- iPhone / iPad / Mac / Android / MS-Windows remote software
- 1 I.E / Firefox for multiple DVRs
- Configuration HTTP / SMTP / FTP / Control / Data port

Specification:

Model		SDVR-1508T	SDVR-1504T
System	O.S	Embedded Linux 3.0	
	Multiplex	Simultaneous record, live, playback, backup, control, & remote access.	
Video	Format	NTSC/EIA or PAL/CCIR	
	Input	8-CH, BNC	4CH, BNC
	Main Monitor	HDMI x 1 / VGA x 1, with resolution up to 1920x1080; BNC x 1, 1Vp-p/75ohm	
Audio	Input	2 RCA-jack connectors, line-in level (100mV-1Vrms, optional)	
	Output	HDMI; 1 RCA-jack connector, line-out level (< 1Vrms)	
Record	Compression	H.264 High Profile; Audio: ADPCM	
	Max. frame rate	960H: 180/150	960H: 120/100
		Full D1: 240/200	Full D1: 120/100
		Half D1 / CIF: 240/200	Half D1/CIF: 120/100
	Mode	Manual/Schedule/Alarm/Motion	
Pre-record time	0-10 Seconds		
Post-record time	0-60 Minutes		
Display	Resolution	HDMI/VGA – up to 1920x1080; NTSC – 720x480, PAL – 720x576	
	Split Windows	1/4/7/9	1/4
	Frame Rate	Up to 30/25 IPS per display window	
	Digital zoom	X2, X4	
Playback	Max. frame rate	960H: 180/150	960H: 120/100
		Full D1: 240/200	Full D1: 120/100
		Half D1 / CIF: 240/200	Half D1/CIF: 120/100
Search	Smart search, Date/time, Camera, Alarm, Motion & Video Loss		
Operation	Play, Fast Forward, Backward, Pause, Stop		
Storage	HDD	1 set of 3.5" SATA HDD with storage >3TB/HDD Failure detection & privacy law supported	
	HDD Extension	-	
	Backup	1 USB 2.0 port; Self playback for backup files	
Alarm	Input	4 contact or TTL/CMOS signal, polarity selectable	
	Output	1 Normally Open or Normally Closed relay output	
Network	Ethernet	1 RJ-45 10/100 BaseT Ethernet connector	
	Function	Free DDNS, Email, FTP, Two-way audio, Audio broadcasting, USB 3G dongle support	
	Remote	Support Windows 8/7/Vista/ XP/2003 1 I.E/Firefox/Chrome/App for unlimited number of DVRs App for Mac/iPhone/iPad/Android phone and Tablet PC	
Control / POS / GPS	Remote Controller	1 remote controller; Optional extension cable	
	RS-232	-	
	RS-485	2-pin for keyboard and /or PTZ control	
Setup	Local	On screen setup via keypad, remote controller, USB mouse, and/or RS-485 keyboard controller	
	Remote	Setup & upload via Windows application software	
Reliability	System recovery	Auto power on after power loss recovery	
	Watch Dog Timer	Yes	
	Timer	Built-in real time clock	
	Security	Multi-level password (4 levels, up to 18 accounts) protection with authentication key for remote access	
Weight & Measures	Dimension	320(W) x 210(D) x 50(H)mm	

	Weight	2.0 KG (without HDD)
Power	Source	+12VDC
	Consumption	30W Max.
Operating Temperature		0oC ~ +40oC

** The specifications are subject to change without notice ** Remarks: NTSC available upon request*